series 49

Weather resistant Polyester TGIC Powder Coatings for **Exterior** and **Interior** Applications.

Features:

Good Weather Resistance Very Smooth Flow Good Storage Stability High Mechanical Properties Good Coverage

Smooth Glossy

All colors featured in this chart are available as standard products in smooth glossy in Series 09, with a gloss level of 80-90*

Smooth Matte, Texture

The following standard products are available for exterior applications:

Black RAL 9011

Smooth Matte	Black RAL 9005	49/80350	20-25*
	White RAL 9010	49/10103	20-25*
	White	49/11350	20-25
Rough Texture Glossy	Nature White	49/11570	

Custom Colors: Colors or Finishes not shown in this chart can be custom made in 7 to 10 days.

49/80990

Datasheets: Periodically updated Series 49 datasheet, showing cure parameters, test results, pretreatment information and more is available. Please contact your local Tiger Drylac office, or visit our web site.

Other exterior colors in smooth glossy, semigloss, matte and texture may also be found in our other color charts:

Series 38 - Super Durable Polyester

Series 39 - Polyester Series 59 - TGIC-Free Institutional Finishes Metallics Special Effects

Specifying RAL Colors: In order to eliminate possible errors in specifying our products, we recommend the use of our product numbers, which not only describe the Series/Chemistry, but also the exact finish selected.

Suggested Example: Tiger Drylac Polyester TGIC RAL 5001, product # 49/42210

Please check with your local Tiger Drylac office for assistance with specifications and suitability issues.

*Gloss level according to Gardner 60 deg., ASTM D 523

offices and warehouses

West Coast 1251 E. Belmont Street

Ontario, CA 91761 Phone: (909) 930-9100 Fax: (909) 930-9111

customerservicewest@tigerdrylac.com

Northwest 18808 142nd Avenue N.E., Suite 5B

Woodinville, WA 98072 Phone: (425) 481-3160 Fax: (425) 481-1136

customerservicenw@tigerdrylac.com

Midwest 3855 Swenson Avenue St. Charles, IL 60174

Phone: (630)513-9999 Fax: (630) 513-9998

customerservicemw@tigerdrylac.com

East Coast 1100 Commons Blvd.

Reading, PA 19605 Phone: (610) 926-8148 Fax: (610) 926-8149

customerserviceeast@tigerdrylac.com

Southeast 3400 Town Pt. Drive NW, Suite 140

Kennesaw, GA 30144 Phone: (770) 218-2490 Fax: (770) 218-2495

customerservicese@tigerdrylac.com

South 339 Exchange Drive

Arlington, TX 76011 Phone: (817) 277-7995 Fax: (817) 277-1931

customerservicesouth@tigerdrylac.com





6/00 • 2003/N






RAL: Having gained worldwide acceptance over the last few decades, the RAL is the most popular Central European Color Standard used today.

The RAL colors in this chart have been matched as closely as possible. Color chart production methods and influence from heat and light may account for slight color deviation from the actual RAL Standard. This chart therefore can not serve as a standard for RAL color production and is to be used as a guide for color planning and specification only.

To aid in final product selection please contact your regional Tiger Drylac location for a powder coated Q-Panel of the product of your choice.



www.tigerdrylac.com

